



技术参数 Specification:

项目 Item	范围 Range	单位 unit	参数值 Value
额定电压 Voltage		V	24
额定转矩 Torque		N.m	0.15
额定转速 Speed	±10%	RRM	4800
额定电流 Current	±10%	A	4.2
功率 Power		W	75
重量 Weight		Kg	1.3

Technical requirements:


1. No tolerance dimensions according to the tolerance standard of GB1804-m.
2. Dielectric strength test at 1200VAC, 2mA, 1S.
3. Axial clearance (two-way) maximum is 0.25mm.
4. The motor rotating flexible Without getting stuck etc. bad phenomenon.

时序图 Timing diagram



前轴伸顺时针方向旋转
CW view from shaft side

线束图 Wiring diagram



Motor Cables:

Pin	Color	Function
1	YELLOW	R phase
2	GREEN	S phase
3	BLUE	T phase
4		Shield

Transducer Cables:

Pin	Color	Function
1	RED	+VCC
2	BLACK	Ground
3	YELLOW	HALL A
4	GREEN	HALL B
5	BLUE	HALL C
6		Shield

BLDC MOTOR				常州宝来电器有限公司 Baolai Electric Appliance			
57SW300				info@baolai-cn.com www.baolai-cn.com			
版本	更改说明	签字	日期	原料标记	数量	比例	
设计	QT	181101	标准化			1:1	
审核							
工艺							
				共 1 张 第 1 张			