


技术参数 Specifications:

技术参数 Specifications:

项目 Item	范围 Range	单位 unit	参数值 Value
额定电压 Voltage		V	24
额定转矩 Torque		N.m	1.1
额定转速 Speed	±10%	RPM	1800
额定电流 Current	±10%	A	12
转矩系数	±10%	N.m/A	0.09
反电势系数	±10%	V/KRPM	8.4
功率 Power		W	200
重量 Weight		Kg	3

接线图 Wiring diagram



Motor Cables

Pin	Color	Function
1	RED	R phase
2	WHITE	S phase
3	BLACK	T phase
4		Shield

Transducer Cables

Pin	Color	Function
1	RED	+VCC
2	BLACK	Ground
3	BROWN	HALL A
4	ORANGE	HALL B
5	YELLOW	HALL C
6		Shield

Technical requirements:

1. No tolerance dimensions according to the tolerance standard of GB1804-m.
2. Dielectric strength test at 1700VAC, 2mA, 1S.
3. Axial clearance(two-way) maximum is 0.1mm.
4. The motor rotating flexible Without getting stuck etc. bad phenomenon.

82SW324		常州宝来电器有限公司 Nantel Electric Appliances	
版本	互连文件号	签字	日期
设计	审核	批准	日期
工艺			
共 1 页 第 1 页		比例 1:1.5	
www.booldi-cn.com		info@booldi-cn.com	